

ASPEN STATIC®

APPLICATIONS

SRT Climbing Line (Single Rope Technique)

BENEFITS / FEATURES

Ultra Low-Stretch Tight Jacket SRT Ascent

Water & Dirt Resistant (Thermo Protector Process)

Similar to Horizon Static *this 11,7 mm static climbing line will provide the perfect diameter for the climber looking for smooth descents and retrieval with multiple redirects with very little effort. This 32 strand kernmantle rope has very low stretch and a thicker cover for reduced wear.

SPECIFICATIONS

Material : Cover: HT Polyester Fiber

Core: HT Polyamide Fiber

Type : A

Specific Gravity : $\sim 1,26 \text{ kg/dm}^3$

Construction : Core: Parallel Braided

Cover: 32 Plaited

UV Resistance : Excellent
Chemical Resistance : Good
Melting Point : 256°C
Critical Temperature : 170°C
Fiber Water Absorption : Approx. %2-3

Wet Abrasion : Good
Dry Abrasion : Good
Standard : EN 1891

Length : 91 M-100 M-183 M-200 M Orange Spool

Other Colours on Request

DIA		Weight		Elongation	Cover	B.Load	
(Inch)	(mm)	(lbs/100ft)	(kg/100m)	(50-150kg)	(%)	(lbs)	(kgf)
15/32"	11,7	7,12	10,60	%1,0	55	7.344	3.331
*Unspliced Break Load (All Tests are in Accordance with ISO 2307)							

